



KNK 50 TRACTOR FRONT TYRE



HIGH TRACTION ABILITY THANKS TO ITS ANGLE BLOCKS

HAS EASY MOVEMENT ABILITY WITH ANTI-GROUND FEATURE THANKS TO BASE PATTERN

PREVENTING CLUSTERS IN THE CENTER AND SIDEWALLS DURING MOVEMENT OF TRACTOR THANKS TO ITS OPEN DESIGN IN CENTER

FACILITATE RELEASING OF MUDS THANKS TO WINDOWED BLOCKS

Code	Tyre Size	PR	Tubeless Tube Type	Rim (Permitted)	Inflated Unloaded Dimensions		Load Index	Speed Index	Load and Pressure	
					Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (kg)	Tyre Pressure (Psi)
3003	7.50-15	8	TUBE TYPE	5,50E	205	780	99	A6	775	52
3122	6.00-16	6	TUBE TYPE	4,50E	165	735	88	A6	560	48
3123	6.00-16	8	TUBE TYPE	4,50E	165	735	93	A6	650	48
3222	6.50-16	6	TUBE TYPE	4,50E	175	760	91	A6	615	45
3223	6.50-16	8	TUBE TYPE	4,50E	175	760	97	A6	730	54
3422	7.50-16	6	TUBE TYPE	5,50F	205	805	98	A6	750	41
3423	7.50-16	8	TUBE TYPE	5,50F	205	805	103	A6	875	54
3442	280/70-16	6	TUBELESS /TUBE TYPE	W9	282	798	102	A6	850	23
3443	280/70-16	8	TUBELESS /TUBE TYPE	W9	282	798	112	A6	1120	35
3523	7.50-18	8	TUBE TYPE	5,50F	205	860	106	A6	950	54
3562	280/70-18	6	TUBELESS	W9	282	849	104	A6	900	23
3563	280/70-18	8	TUBELESS	W9	282	849	114	A6	1180	35
3623	7.50-20	8	TUBE TYPE	5,50F	205	915	108	A6	1000	49
3643	8.00-20	8	TUBE TYPE	5,50F	220	965	111	A6	1090	41
3663	9.5-20	8	TUBELESS /TUBE TYPE	W8	241	940	106	A6	950	35
3683	11.2-20	8	TUBELESS /TUBE TYPE	W10	285	1005	113	A6	1150	38



Http Error Page
Error Message:

Return to the [Default Page](#)